

CHISEL PLOUGH



HR1200 & RIGID TYNE CHISEL PLOUGH

Gessner offers both HR1200 Hydraulic Release Tyne and Rigid Tyne Chisel Ploughs, ensuring that all of your Broadacre ground preparation requirements are catered for. The combination of heavy-duty frame and quality, field-proven units provides unmatched durability and longevity in tough tillage conditions.

RIGID TYNE CHISEL PLOUGH

- Rigid tyne frames range from 10ft (3.0m) to 42ft (12.8m)
- The specially designed multi-section frame is available in a single-fold hydraulic configuration for machines 22ft and above. Alternatively rigid, trailing frame configurations are available from 10ft to 28ft depending on application requirements.

Various wheel configurations are available depending on frame width:

- 7.50 x 16 Compactor Tyres on 10ft – 12ft machines;
- 10.00 x 16 x 8 Ply Stabiliser Tyres on 16ft machines;
- 15R x 22.5 Super Single Tyres on 20ft – 28ft machines;
- All wings feature 10.00 x 20 Truck Tyres.
- Safety Chains for 34ft frame configurations and above.

HR1200 CHISEL PLOUGH

- HR1200 frames range from 10ft (3.0m) to 54ft (16.4m).
- The heavy duty multi-section frame is available in a single-fold configuration or as a rigid, trailing frame depending on machine width and application requirements.
- Specially designed heavy duty hydraulic release tynes feature high-quality jump cylinders.
- Hydraulic phasing depth wheels varying in size depending on frame configuration:
 - 15R x 22.5 Super Singles on 4.8m Centre Sections;
 - 49 x 17 x 30 Aero Tyres on 6.1m Centre Sections;
 - All wings feature 10.00 x 20 Truck Tyres.
- Safety chains feature on 42ft frame configurations and above.

